

Indiana Limestone Gray



Description:

Indiana Limestone is one of the most widely-used, natural stones in the world. It is neutral in color and almost without blemish. The color range is a warm white (or buff) tone. This limestone has no discernable grain structure, giving it equal physical strength in all directions. Combined with a high resistance to deterioration from weather and pollution, this stone is a great choice for any application where natural stone and crisp detail edges are desired.

Characteristics:

Compressive Strength: 4,000 psi (ASTM C170)

Modulus of Rupture: 700 psi (ASTM C99)

Absorption: 7.5% (ASTM C97)

Bulk Specific Gravity: 2.1 to 2.75

Density: 144 lbs/cubic ft.

Note: Physical properties are provided for general comparisons. For specific applications and design engineering please contact your Lang Sales Representative for current ASTM testing data.

Applications:

Indiana Limestone is used for a wide range of structural and detail building stone applications including; columns, veneer panels, balustrade, ornate accent work, sills, lintels and more.

*Visit our Product Gallery at
www.langstone.com for more ideas.*

LANG
STONE

Since 1856

707 Short St., Columbus, OH 43215

614/228-5489 • 1-800/589-LANG

Hours: M-F 7:30 - 5 / Sat. 8 - Noon

www.langstone.com

© 2009 Lang Stone Co. Version 5-09

